

Simply Cool Keyboard

The Simply Cool is a full size water-resistant and contaminant proof keyboard with tactile feedback keys. This sealed and rigid surface keyboard is value priced for industrial, marine, and medical use, as well as other applications where moisture and cleaning are a consideration. Because the Simply Cool is also quieter than "standard" keyboards, they are great for applications where noise generated from "key-clicks" is a problem. The Simply Cool is compatible with standard keyboard layouts and drivers are not needed.

Weight: 454.0 g (1.0 lb.)	Composition: 100% Silicone Rubber
Dimensions: 381 mm x 140 mm x 8.0 mm 15" x 5.5" x 0.3"	PVC Cable 100% Latex free
Cable length: 1.83 m (6')	System requirements: USB interface PS/2 interface (USB to PS/2 Adapter Not Included)
Storage temperature: -20 °C - 70 °C -4 °F - 158 °F	Number of keys: 102 US Layout keys with keypad.
Operating temperature: 0 °C - 70 °C 32 °F - 158 °F	Warranty period: One year replacement warranty.
Voltage: 5 Volt	Specifications subject to change without notice
Current input: 26 mA	

Installing Your Simply Cool Keyboard

- USB:** Attach the keyboard cable to a USB computer port. (You do not have to turn off your computer. There is no software to install.)
- PS2:** Turn off your computer before attaching devices. If you have another keyboard attached, disconnect it. Attach the PS2 keyboard Adapter (sold separately) to USB cable connector. Attach cable to the keyboard port. Turn on your computer to activate the keyboard. (There is no software to install.)

You can email us at: info@mmimd.com
or call us at: (301) 341-4900
In Europe, contact +31-23-5450185
www.man-machine.com



Cleaning Instructions for Waterproof Keyboards and Mice:

1. Clean the surface of the product by wiping, brushing, spraying or dipping it. Use only rags, sponges or soft bristle brushes. **DO NOT place the USB or PS/2 connector into the fluid.**
2. Either wipe with dry cloth or allow to air dry.

Disinfectants recommended by Man & Machine, Inc.:

- Chlorine based (max 10% solution) - Chlorox, Novalsan, etc.
- Formaldehyde based - Formaldehyde Solution 37%, Vinco Formaldegen, etc.
- Glutaraldehyde based - Aldacide 200, Lysofume, Wavicide, etc.
- Phenol based - Lysol I.C., Beaucoup, Magna Clean, Tek-Trol, etc.
- Alcohol based - Cavicide, Isopropyl Alcohol, Medicide, etc.
- Oxidizing - Hydrogen Peroxide 3% Solution, Lifeguard Series, etc.
- Quaternary Ammonium - Roccal-D, Bacto-Sep, Parvosol, etc.
- Soap and water

DO NOT USE:

- Petroleum based cleaning fluids, such as Gasoline
- Acetone
- Over 10% bleach solutions
- Temperature or pressure sterilization
- Buffing pads or scrubbing pads

THESE INSTRUCTIONS AND RECOMMENDATIONS HAVE BEEN PREPARED TO ADVISE THE PROPER METHODS FOR CLEANING YOUR PRODUCT. MAN & MACHINE, INC. OR THE LOCAL DISTRIBUTOR CANNOT ASSUME ANY RESPONSIBILITY FOR THE APPLICATION OF THEM. IF THERE ARE ANY QUESTIONS, PLEASE CONTACT PLACE OF PURCHASE OR MMI PRIOR TO CLEANING.



Copyright Man & Machine, Inc. 2007